



DT-101SK

Order No.: 10.0060

EUR 36,90

RRP *

PRODUCTINFOS

Hi-fi dome tweeter, 30 W, 8 Ω

- Silk dome with optimum damping
- Attached, damped volume
- High linearity up to the brilliance frequency range
- Very good efficiency
- High-resolution sound
- For hi-fi applications of high requirements

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	
Frequency range	fx-22,000 Hz
Resonant frequency (fs)	900 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz
Music power (P_{MAX})	50 W_{MAX}
Power rating (P_{RMS})	30 W_{RMS}
Sensitivity	92 dB
Max. rated SPL	
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	
Moving mass (Mms)	
Mech. Q factor (Qms)	
Electr. Q factor (Qes)	
Total Q factor (Qts)	
Equivalent volume (Vas)	
DC resistance (Re)	
Force factor (BxL)	
Voice coil induct. (Le)	
Voice coil diameter	
Voice coil former	
Linear excursion (X_{MAX})	
Eff. cone area (Sd)	
Magnet weight	
Magnet diameter	70 mm
Mounting cutout	Ø 80 mm
Mounting depth	46 mm
Mounting hole diameter	
Hole spacing X	
Hole spacing Y	
Dimensions	
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	
Weight	0.5 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.