



DT-250

Order No.: 10.0090

EUR 62,90

RRP *

PRODUCTINFOS

Hi-fi dome tweeter, 50 W, 8 Ω

- Light metal titanium alloy
- Perfect damping due to rubber surround and without resonant behaviour typical for metal
- Fine sound, comfortable to listen to
- Classic rectangular size

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	
Frequency range	fx-25,000 Hz
Resonant frequency (fs)	1,700 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	3,000 Hz

Music power (P_{MAX})	100 W _{MAX}
Power rating (P_{RMS})	50 W _{RMS}
Sensitivity	90 dB
Max. rated SPL	
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	
Moving mass (Mms)	
Mech. Q factor (Qms)	
Electr. Q factor (Qes)	
Total Q factor (Qts)	
Equivalent volume (Vas)	
DC resistance (Re)	
Force factor (BxL)	
Voice coil induct. (Le)	
Voice coil diameter	25 mm
Voice coil former	
Linear excursion (X_{MAX})	
Eff. cone area (Sd)	
Magnet weight	
Magnet diameter	72 mm
Mounting cutout	Ø 74 mm
Mounting depth	26 mm
Mounting hole diameter	
Hole spacing X	
Hole spacing Y	
Dimensions	116x86 mm
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	
Weight	0.55 kg
Quantity	

shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.