



DT-99

Order No.: 10.3880

EUR 32,90

RRP *

PRODUCTINFOS

Hi-fi dome tweeter, 40 W, 8 Ω

- Pure silk cone
- Excellent radiation
- Very typical sound pressure curve
- For replacement purposes and hi-fi applications

TECHNICAL SPECIFICATIONS

| | |
|--|--------------|
| Impedance (Z) | 8 Ω |
| Operating voltage | |
| Frequency range | fx-18,000 Hz |
| Resonant frequency (fs) | 1,500 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | 2,500 Hz |

| | |
|--------------------------------|---------------------|
| Music power (P_{MAX}) | 80 W _{MAX} |
| Power rating (P_{RMS}) | 40 W _{RMS} |
| Sensitivity | 93 dB |
| Max. rated SPL | |
| Max. voltage | |
| Radiation angle | |
| Suspension compl. (Cms) | |
| Moving mass (Mms) | |
| Mech. Q factor (Qms) | |
| Electr. Q factor (Qes) | |
| Total Q factor (Qts) | |
| Equivalent volume (Vas) | |
| DC resistance (Re) | |
| Force factor (BxL) | |
| Voice coil induct. (Le) | |
| Voice coil diameter | 25 mm |
| Voice coil former | |
| Linear excursion (X_{MAX}) | |
| Eff. cone area (Sd) | |
| Magnet weight | |
| Magnet diameter | 70 mm |
| Mounting cutout | Ø 72 mm |
| Mounting depth | 35 mm |
| Mounting hole diameter | |
| Hole spacing X | |
| Hole spacing Y | |
| Dimensions | Ø 100 mm |
| Outside diameter | |
| Width | |
| Height | |
| Depth | |
| Admiss. ambient temp. | |
| Weight | 520 g |
| Quantity | |

shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.