



## HT-958PA/SW

Order No.: 10.2450

**EUR 42,90**

RRP \*

### PRODUCTINFOS

**Ring radiator tweeter, 30 W, 8  $\Omega$**

- For PA and hi-fi
- High efficiency
- Very wide bandwidth radiation with an excellent linearity

### TECHNICAL SPECIFICATIONS

Impedance (Z)	8 $\Omega$
Operating voltage	-
Frequency range	fx-20 kHz
Resonant frequency (fs)	2.2 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	5 kHz

Music power ( $P_{MAX}$ )	60 W
Power rating ( $P_{RMS}$ )	30 W
Sensitivity	101 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	45°/45°
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø 25.4 mm
Voice coil former	-
Linear excursion ( $X_{MAX}$ )	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 70 mm
Mounting cutout	Ø 72 mm
Mounting depth	45 mm
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 97 mm x 45 mm
Outside diameter	Ø 97 mm
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	0.55 kg
Quantity	1

shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.