



MHD-220N/RD

Order No.: 10.5080

EUR 62,90

RRP *

PRODUCTINFOS

PA horn tweeter, 30 W, 8 Ω

- Very compact and lightweight horn tweeter
- NEODYMIUM drive system with ferrofluid cooling
- Titanium cone
- Round ABS plastic horn front attachment with a very linear reproduction of low distortion
- High efficiency
- Interesting tweeter for PA and DJ applications
- For speaker systems of high efficiency in PA applications and hi-fi systems

HOBBY HiFi 05/2014

"... provides a brilliant sound quality, an amazing level stability and an exceptionally high efficiency - a real insider tip."

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	fx-20,000 Hz
Resonant frequency (fs)	2.3 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	5,000 Hz
Music power (P _{MAX})	75 W
Power rating (P _{RMS})	30 W
Sensitivity	104 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	75°/75°
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	-
Voice coil former	-
Linear excursion (X _{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 65 mm
Mounting cutout	Ø 75 mm
Mounting depth	67 mm
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 106 mm x 67 mm
Outside diameter	-
Width	-
Height	-

Depth	-
Admiss. ambient temp.	0-40 °C
Weight	220 g
Quantity	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.