



MHD-230/RD

Order No.: 10.3430

EUR 52,90

RRP *

PRODUCTINFOS

Horn Tweeters

High-quality workmanship, with robust plastic horns, mainly made of ABS, in some cases glass fibre reinforced.

PA horn tweeter, 40 W, 8 Ω

- Round horn of perfect workmanship
- Extra high efficiency
- Excellent radiation
- Suitable for any DJ and PA application up to professional use
- Replacement voice coil MHD-230/VC is available at option

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	fx-16,000 Hz
Resonant frequency (fs)	1,100 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	4,000 Hz
Music power (P _{MAX})	80 W
Power rating (P _{RMS})	40 W
Sensitivity	109 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	60°/60°
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø 25 mm
Voice coil former	-
Linear excursion (X _{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 90 mm
Mounting depth	120 mm
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 120 mm x 120 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C

Weight	0.9 kg
Quantity	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.