



## MHD-230/SQ

Order No.: 10.3440

**EUR 52,90**

RRP \*

### PRODUCTINFOS

#### PA horn tweeter, 40 W, 8 $\Omega$

- Square horn of perfect workmanship
- Extra high efficiency
- Excellent radiation
- Suitable for any DJ and PA application up to professional use
- Replacement voice coil MHD-230/VC is available at option

#### Horn Tweeters

High-quality workmanship, with robust plastic horns, mainly made of ABS, in some cases glass fibre reinforced.

### TECHNICAL SPECIFICATIONS

Impedance (Z)	8 $\Omega$
Operating voltage	-
Frequency range	fx-16,000 Hz
Resonant frequency (fs)	1,300 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	4000 Hz
Music power (P <sub>MAX</sub> )	80 W
Power rating (P <sub>RMS</sub> )	40 W
Sensitivity	110 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	60°/60°
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	25 mm
Voice coil former	-
Linear excursion (X <sub>MAX</sub> )	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 80 mm
Mounting cutout	90 x 90 mm
Mounting depth	115 mm
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	115 x 115 x 115 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C

Weight	0.9 kg
Quantity	1

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.