



MHD-240

Order No.: 10.3890

EUR 62,90

RRP *

PRODUCTINFOS

Horn Tweeters

High-quality workmanship, with robust plastic horns, mainly made of ABS, in some cases glass fibre reinforced.

PA horn tweeter, 40 W, 8 Ω

- CD horn tweeter (constant directivity)
- Very wide bandwidth reproduction
- Very good medium efficiency
- Special horn design
- Diecast reflector in front of the cone
- Highly consistent radiation pattern
- Suitable for any PA application
- Replacement voice coil MHD-230/VC is available at option

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	fx-20,000 Hz
Resonant frequency (fs)	2 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	3.5 kHz
Music power (P _{MAX})	80 W
Power rating (P _{RMS})	40 W
Sensitivity	107 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	40°/90°
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø 25 mm
Voice coil former	-
Linear excursion (X _{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 80 mm
Mounting cutout	120 x 157 mm
Mounting depth	130 mm
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	205 x 163 x 130 mm
Outside diameter	-
Width	-
Height	-

Depth	-
Admiss. ambient temp.	0-40 °C
Weight	1.135 kg
Quantity	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.