



MRD-160

Order No.: 10.4370

EUR 104,90

RRP *

PRODUCTINFOS

PA mid-high range driver, 60 W, 8 Ω

- Top-class 25 mm (1") professional driver
- Reproduction of high efficiency and very linear frequency response
- Very compact size, high power capability
- For PA speaker systems of high requirements, perfectly suitable for combination with 30 cm and 25 cm (12" and 10") bass speakers
- The replacement voice coil SP-30PAX/VC is available at option
- Suitable for the horns MRH-200 and MRH-180

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	fx-18,000 Hz

Resonant frequency (fs)	750 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz
Music power (P _{MAX})	150 W
Power rating (P _{RMS})	60 W
Sensitivity	109 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø 44.4 mm
Voice coil former	-
Linear excursion (X _{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 110 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 115 mm x 53 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	1.7 kg
Quantity	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.