



## MRD-180

Order No.: 10.4380

**EUR 129,90**

RRP \*

### PRODUCTINFOS

#### PA mid-high range driver, 80 W, 8 $\Omega$

- Top-class professional 25 mm (1") driver
- Phenomenal wide bandwidth reproduction of high efficiency and linear frequency response
- Of compact size and yet of high power capability
- Perfect in any demanding PA speaker system, as long as 50 mm (2") drivers are not required
- The replacement voice coil SP-30PAX/VC is available at option
- Suitable for the horns MRH-200 and MRH-180

### TECHNICAL SPECIFICATIONS

Impedance (Z)	8 $\Omega$
Operating voltage	-
Frequency range	fx-19,000 Hz
Resonant frequency (fs)	800 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	1,800 Hz
Music power (P <sub>MAX</sub> )	180 W
Power rating (P <sub>RMS</sub> )	80 W
Sensitivity	109 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	dep. on horn
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø 44 mm
Voice coil former	-
Linear excursion (X <sub>MAX</sub> )	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø 130 mm
Mounting cutout	dep. on horn
Mounting depth	-
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 134 mm x 58 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	2.75 kg
Quantity	1

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.