



## MRD-25PA

Order No.: 10.1900

**EUR 33,90**

RRP \*

### PRODUCTINFOS

#### PA horn driver, 25 W, 8 $\Omega$

- Compact 25 mm (1") horn driver with ferrite magnets
- Titanium cone with 25 mm voice coil
- Standard 35 mm ( $\frac{38}{16}$ " ) thread
- Suitable for the horns MRH-83, MRH-80; with adapter MHA-25 also for others
- Matching replacement voice coil MRD-25PA/VC available at option

### TECHNICAL SPECIFICATIONS

Impedance (Z)	8 $\Omega$
Operating voltage	-
Frequency range	fx-20,000 Hz
Resonant frequency (fs)	2 kHz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	4,000 Hz
Music power ( $P_{MAX}$ )	50 W
Power rating ( $P_{RMS}$ )	25 W
Sensitivity	100 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	dep. on horn
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø 100 mm
Voice coil former	-
Linear excursion ( $X_{MAX}$ )	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	78 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 80 mm x 65 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	0.673 kg
Quantity	1

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.