



MSH-115HQ

Order No.: 10.1330

EUR 69,90

RRP *

PRODUCTINFOS

High-quality hi-fi midrange speaker, 50 W, 8 Ω

- 100 mm (4") midrange speaker
- Further development of the classic speaker MSH-115
- Specialised for reproduction of the important midrange
- Diecast basket and rear-ventilated centering spider for minimum mechanical loss
- High-quality, low-resonance paper cone
- Wide and linear radiation range
- Also ideally suited for application in small satellite systems with subwoofer support

High-quality hi-fi speakers

for highest sound requirements. The well-known and successful speakers of the SPH series and MSH series are now available with innovative diecast aluminium baskets, rear-ventilated centering spiders and optimised parameters.

HOBBY HiFi 01/2013

"Smooth, very fast decay. Impresses with its high-quality workmanship."

Klang+Ton 02/2013

SPH-10M, MSH-115HQ, RBT-95SR and SAM-2 in the building concept 2DOT1

"A system of appealing design which provides an equally nice sound ... the speaker building concept features an amazing adaptability and almost unlimited settings ... incredibly suitable for everyday use, is capable of reproducing any kind of music and suitable for home cinema systems. The system provided an absolutely amazing sound when tested in the audio room. The small speakers appeared to reproduce the complete bass range. There was no way of locating the subwoofer. The tactics with the tiles achieved great results ... nothing trembles, even though a powerful bass speaker of a high power capability is set-up in the room. The satellites provide an extra light and high-resolution sound."

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	
Frequency range	fx-8,000 Hz
Resonant frequency (fs)	89 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-
Music power (P _{MAX})	100 W
Power rating (P _{RMS})	50 W
Sensitivity	87 dB
Max. rated SPL	
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.5 mm/N
Moving mass (Mms)	5.8 g
Mech. Q factor (Qms)	3.26
Electr. Q factor (Qes)	0.66
Total Q factor (Qts)	0.55
Equivalent volume (Vas)	2.2 l
DC resistance (Re)	5.8 Ω
Force factor (BxL)	5.35 Tm
Voice coil induct. (Le)	0.53 mH
Voice coil diameter	25 mm
Voice coil former	aluminium
Linear excursion (X _{MAX})	± 3 mm

Eff. cone area (Sd)	55 cm ²
Magnet weight	230 g
Magnet diameter	-
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	-
Hole spacing X	-
Hole spacing Y	-
Dimensions	-
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	
Weight	0.67 kg
Quantity	-

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.