



SP-100/8

Order No.: 10.3780

EUR 35,90

RRP *

PRODUCTINFOS

Hi-fi bass-midrange speaker, 30 W, 8 Ω

- Robust paper cone
- High-quality aluminium coil
- Drilled pole core
- Rubber surround
- Excellent radiation and transient response

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	
Frequency range	f3-7,000 Hz
Resonant frequency (fs)	61 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P_{MAX})	60 W_{MAX}
Power rating (P_{RMS})	30 W_{RMS}
Sensitivity	88 dB/W/m
Max. rated SPL	
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	1.23 mm/N
Moving mass (Mms)	5.5 g
Mech. Q factor (Qms)	2.28
Electr. Q factor (Qes)	0.44
Total Q factor (Qts)	0.37
Equivalent volume (Vas)	4.7 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	5.55 Tm
Voice coil induct. (Le)	0.4 mH
Voice coil diameter	25 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 2.5 mm
Eff. cone area (Sd)	52 cm ²
Magnet weight	280 g
Magnet diameter	
Mounting cutout	
Mounting depth	
Mounting hole diameter	
Hole spacing X	
Hole spacing Y	
Dimensions	
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	
Weight	0.8 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.