



SP-15/300PA

Order No.: 10.2540

EUR 185,00

RRP *

PRODUCTINFOS

High-Quality PA Speakers

For general stage and professional DJ applications. Excellent workmanship and perfect specifications for bass-reflex speaker systems of high power capability.

PA bass speaker, 300 W, 8 Ω

- Very high efficiency for bass applications
- Maximum bass pressure in the medium bass range in astonishingly small cabinets

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-4,500 Hz

Resonant frequency (fs)	38 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-
Music power (P _{MAX})	600 W
Power rating (P _{RMS})	300 W
Sensitivity	101 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.23 mm/N
Moving mass (Mms)	88 g
Mech. Q factor (Qms)	5.44
Electr. Q factor (Qes)	0.29
Total Q factor (Qts)	0.27
Equivalent volume (Vas)	232 l
DC resistance (Re)	6.8 Ω
Force factor (BxL)	22.2 Tm
Voice coil induct. (Le)	1.3 mH
Voice coil diameter	78 mm
Voice coil former	Kapton
Linear excursion (X _{MAX})	±3 mm
Eff. cone area (Sd)	855 cm ²
Magnet weight	1.8 kg
Magnet diameter	Ø 180 mm
Mounting cutout	Ø 358 mm
Mounting depth	146 mm
Mounting hole diameter	-
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	Ø 388 mm x 156 mm
Outside diameter	Ø 388 mm
Width	388 mm
Height	388 mm
Depth	156 mm
Protective class	
Admiss. ambient temp.	0-40 °C
Weight	7 kg

Quantity 1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.