



SP-150

Order No.: 10.0320

EUR 57,90

RRP *

PRODUCTINFOS

Universal speaker, 30 W, 8 Ω

- White polypropylene cone
- Basket with plastic trim ring

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-4,000 Hz
Resonant frequency (fs)	35 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P _{MAX})	60 W

Power rating (P_{RMS})	30 W
Sensitivity	90 dB/W/m
Max. rated SPL	-
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	1.56 mm/N
Moving mass (Mms)	10.4 g
Mech. Q factor (Qms)	2.83
Electr. Q factor (Qes)	0.61
Total Q factor (Qts)	0.50
Equivalent volume (Vas)	35 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	7.5 Tm
Voice coil induct. (Le)	0.45 mH
Voice coil diameter	25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 2.5 mm
Eff. cone area (Sd)	127 cm ²
Magnet weight	380 g
Magnet diameter	
Mounting cutout	\varnothing 145mm
Mounting depth	75 mm
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	\varnothing 170 mm x 75 mm
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	0-40 °C
Weight	1.2 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.