



## SP-200X

Order No.: 10.0400

**EUR 77,90**

RRP \*

### PRODUCTINFOS

**Hi-fi full range speaker, 35 W, 8  $\Omega$**

- One-piece rubber gasket
- Very good linearity
- High efficiency
- For PA systems of special sound requirements or in large column speakers

**HOBBY HiFi 01/2012**

"The SPH-200X impresses by an excellent sound quality."

### TECHNICAL SPECIFICATIONS

Impedance (Z)                      8  $\Omega$

Operating voltage

Frequency range	f3-15,000 Hz
Resonant frequency (fs)	50 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P <sub>MAX</sub> )	70 W
Power rating (P <sub>RMS</sub> )	35 W
Sensitivity	92 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.77 mm/N
Moving mass (Mms)	11.5 g
Mech. Q factor (Qms)	1.96
Electr. Q factor (Qes)	0.7
Total Q factor (Qts)	0.52
Equivalent volume (Vas)	48 l
DC resistance (Re)	7.2 Ω
Force factor (BxL)	6.1 Tm
Voice coil induct. (Le)	0.3 mH
Voice coil diameter	25.5 mm
Voice coil former	aluminium
Linear excursion (X <sub>MAX</sub> )	±1.6 mm
Eff. cone area (Sd)	210 cm <sup>2</sup>
Magnet weight	500 g
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	Ø 205 mm x 80 mm
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	
Weight	1.3 kg

Quantity

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.