



SP-6/150PA

Order No.: 10.3180

EUR 49,90

RRP *

PRODUCTINFOS

PA midrange speaker, 150 W, 8 Ω

- For PA midrange applications requiring a high power capability with simultaneous use of mid-high range horns
- Very well-suited for dual arrangements

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-6,000 Hz
Resonant frequency (fs)	73 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-

Music power (P_{MAX})	300 W _{MAX}
Power rating (P_{RMS})	150 W _{RMS}
Sensitivity	93 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.31 mm/N
Moving mass (Mms)	15.2g
Mech. Q factor (Qms)	5.31
Electr. Q factor (Qes)	0.46
Total Q factor (Qts)	0.42
Equivalent volume (Vas)	8.5 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	9.9 Tm
Voice coil induct. (Le)	0.6 mH
Voice coil diameter	50 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	± 1 mm
Eff. cone area (Sd)	139 cm ²
Magnet weight	850 g
Magnet diameter	\varnothing 120 mm
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	-
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	\varnothing 170 mm x 86 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	2.1 kg
Quantity	1

shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.