



SP-8/150PA

Order No.: 10.1680

EUR 64,90

RRP *

PRODUCTINFOS

PA bass-midrange speaker, 150 W, 8 Ω

- Good medium efficiency
- Wide bandwidth radiation for midrange applications

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-8,000 Hz
Resonant frequency (fs)	88 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-
Music power (P _{MAX})	300 W _{MAX}

Power rating (P_{RMS})	150 W_{RMS}
Sensitivity	96 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.16 mm/N
Moving mass (Mms)	20 g
Mech. Q factor (Qms)	4.12
Electr. Q factor (Qes)	0.48
Total Q factor (Qts)	0.43
Equivalent volume (Vas)	12 l
DC resistance (Re)	6.9 Ω
Force factor (BxL)	12.6 Tm
Voice coil induct. (Le)	0.6 mH
Voice coil diameter	50 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	± 1.25 mm
Eff. cone area (Sd)	219 cm^2
Magnet weight	1.1 kg
Magnet diameter	\varnothing 140 mm
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	-
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	\varnothing 210 mm x 98 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 $^{\circ}C$
Weight	3 kg
Quantity	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.