



SPH-130AL

Order No.: 10.3820

EUR 79,90

RRP *

PRODUCTINFOS

Hi-fi bass-midrange speaker, 50 W, 8 Ω

- All-aluminium cone and dustcap
- Special design for extra reinforcement
- 6-hole screw connection
- Extra dynamic sound and a very wide bandwidth
- Midrange speaker of high efficiency and high power capability for high-end speaker systems and a perfect bass-midrange speaker for small speaker systems

HOBBY HiFi 04/2012

"The SPH-130AL impresses by an excellent sound quality and is suitable for particularly wideband applications ... frequencies up to 4 kHz can be utilised, one of the top marks in the test field."

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	
Frequency range	f3-4,500 Hz
Resonant frequency (fs)	48 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P _{MAX})	100 W _{MAX}
Power rating (P _{RMS})	50 W _{RMS}
Sensitivity	88 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	1.2 mm/N
Moving mass (Mms)	9 g
Mech. Q factor (Qms)	5.07
Electr. Q factor (Qes)	0.34
Total Q factor (Qts)	0.32
Equivalent volume (Vas)	10.8 l
DC resistance (Re)	6.4 Ω
Force factor (BxL)	7.22 Tm
Voice coil induct. (Le)	0.6 mH
Voice coil diameter	25 mm
Voice coil former	Kapton
Linear excursion (X _{MAX})	± 2.3 mm
Eff. cone area (Sd)	80 cm ²
Magnet weight	440 g
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X	
Hole spacing Y	
Dimensions	\varnothing 155 mm x 70 mm
Outside diameter	
Width	

Height

Depth

Admiss. ambient temp.

Weight 1 kg

Quantity

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.