



SPH-170

Order No.: 10.0110

EUR 94,90

RRP *

PRODUCTINFOS

Hi-fi bass-midrange speaker, 50 W, 8 Ω

- Speakers of very high quality with extensive equipment
- Round aluminium diecast basket with recessed screw head holes
- Inverse rubber surround
- Drilled pole core
- Cone with excellent damping
- Exceptionally deep bass reproduction for any bass and bass-midrange application

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-5,000 Hz
Resonant frequency (fs)	38 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P_{MAX})	80 W_{MAX}
Power rating (P_{RMS})	50 W_{RMS}
Sensitivity	90 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	1.43 mm/N
Moving mass (Mms)	12.5 g
Mech. Q factor (Qms)	2.38
Electr. Q factor (Qes)	0.55
Total Q factor (Qts)	0.44
Equivalent volume (Vas)	37 l
DC resistance (Re)	6.2 Ω
Force factor (BxL)	5.9 Tm
Voice coil induct. (Le)	0.45 mH
Voice coil diameter	25 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 3 mm
Eff. cone area (Sd)	137 cm ²
Magnet weight	370 g
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	\varnothing 185 mm x 80 mm
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	0-40 °C
Weight	1.32 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.