



SPH-200TC

Order No.: 10.1690

EUR 89,90

RRP *

PRODUCTINFOS

Hi-fi bass speaker and subwoofer, 2 x 60 W, 2 x 8 Ω

- High-quality polypropylene cone
- Dual voice coil
- Set of parameters for an astonishingly deep and powerful bass reproduction from very small bass-reflex cabinets
- Very well-suited for slim column speakers with integrated subwoofer

TECHNICAL SPECIFICATIONS

| | |
|-------------------------|----------------|
| Impedance (Z) | 2 x 8 Ω |
| Operating voltage | - |
| Frequency range | f3-4,000 Hz |
| Resonant frequency (fs) | 28 Hz |

| | |
|--|---------------------------------|
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | |
| Music power (P_{MAX}) | 2 x 100 W_{MAX} |
| Power rating (P_{RMS}) | 2 x 60 W_{RMS} |
| Sensitivity | 88 dB |
| Max. rated SPL | - |
| Max. voltage | - |
| Radiation angle | - |
| Suspension compl. (Cms) | 1.01 mm/N |
| Moving mass (Mms) | 32 g |
| Mech. Q factor (Qms) | 6.19 |
| Electr. Q factor (Qes) | 0.25 |
| Total Q factor (Qts) | 0.24 |
| Equivalent volume (Vas) | 65 l |
| DC resistance (Re) | 2 x 6.8 Ω / 3.4 Ω |
| Force factor (BxL) | 8.9 Tm |
| Voice coil induct. (Le) | 2 x 1.0 mH/ 1.0 mH |
| Voice coil diameter | 50 mm |
| Voice coil former | Kapton |
| Linear excursion (X_{MAX}) | ± 3.75 mm |
| Eff. cone area (Sd) | 210 cm ² |
| Magnet weight | 840 g |
| Magnet diameter | |
| Mounting cutout | - |
| Mounting depth | - |
| Mounting hole diameter | |
| Hole spacing X | - |
| Hole spacing Y | - |
| Dimensions | \varnothing 210 mm x 102 mm |
| Outside diameter | |
| Width | |
| Height | |
| Depth | |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 2.6 kg |
| Quantity | |

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.