



SPH-300CTC

Order No.: 10.1830

EUR 225,00

RRP *

PRODUCTINFOS

Hi-fi subwoofer, 2 x 150 W, 2 x 8 Ω

- High-end speaker with diecast basket
- Dual voice coil
- Carbon fibre cone
- Powerful bass reproduction from bass-reflex cabinets or an especially dry, pulsed sound from very small closed cabinets
- For hi-fi, home cinema and top car hi-fi

Thiele Small parameters and sound pressure curves for voice coils in parallel or series connection.

HOBBY HiFi 04/2015

"Despite being content with a moderate cabinet size, it still provides a superior deep bass due to the powerful drive system."

TECHNICAL SPECIFICATIONS

Impedance (Z)	2 x 8 Ω
Operating voltage	-
Frequency range	f3-2,500 Hz
Resonant frequency (fs)	18 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P _{MAX})	2 x 250 W _{MAX}
Power rating (P _{RMS})	2 x 150 W _{RMS}
Sensitivity	92 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.75 mm/N
Moving mass (Mms)	100 g
Mech. Q factor (Qms)	6.50
Electr. Q factor (Qes)	0.20
Total Q factor (Qts)	0.19
Equivalent volume (Vas)	225 l
DC resistance (Re)	2 x 6 Ω /3 Ω
Force factor (BxL)	12.1 Tm
Voice coil induct. (Le)	2 x 1.1 mH/1.1 mH
Voice coil diameter	62 mm
Voice coil former	Kapton
Linear excursion (X _{MAX})	\pm 5.4 mm
Eff. cone area (Sd)	495 cm ²
Magnet weight	1.8 kg
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	\varnothing 308 mm x 130 mm
Outside diameter	
Width	

Height

Depth

Admiss. ambient temp. 0-40 °C

Weight 6.0 kg

Quantity

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.