



SPH-300TC

Order No.: 10.1460

EUR 119,90

RRP *

PRODUCTINFOS

Hi-fi subwoofer, 2 x 120 W_{RMS}, 2 x 8 Ω

- Stabilised polypropylene cone
- Dual voice coil
- Perfect parameters for a deep bass reproduction in compact bass-reflex cabinets and band-pass cabinets
- For any hi-fi, home cinema and car hi-fi application of high requirements

TECHNICAL SPECIFICATIONS

Impedance (Z)	2 x 8 Ω
Operating voltage	-
Frequency range	f3-2,000 Hz
Resonant frequency (fs)	23 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P_{MAX})	2 x 250 W _{MAX}
Power rating (P_{RMS})	2 x 120 W _{RMS}
Sensitivity	91 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.85 mm/N
Moving mass (Mms)	68 g
Mech. Q factor (Qms)	3.03
Electr. Q factor (Qes)	0.26
Total Q factor (Qts)	0.24
Equivalent volume (Vas)	290 l
DC resistance (Re)	2 x 6.3 Ω /3.2 Ω
Force factor (BxL)	10.3 Tm
Voice coil induct. (Le)	2 x 1.0 mH/1.0 mH
Voice coil diameter	50 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 4 mm
Eff. cone area (Sd)	495 cm ²
Magnet weight	1.4 kg
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	\varnothing 306 mm x 140 mm
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	0-40 °C
Weight	4.0 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.