



SPH-380TC

Order No.: 10.3260

EUR 315,00

RRP *

PRODUCTINFOS

Subwoofer, 2 x 250 W, 2 x 4 Ω

- 40 cm (15") subwoofer of highest power capability, dual voice coil technology
- Extra small volume requirements
- Robust complete cone with new geometry for highest rigidity and an excellent dynamic response
- Extra long excursion
- Rubber surround
- Extensive air gap ventilation
- For general subwoofer applications from home cinema to compact DJ subwoofers

TECHNICAL SPECIFICATIONS

Impedance (Z)	2 x 4 Ω
Operating voltage	-
Frequency range	f3-800 Hz

Resonant frequency (fs)	21.5 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P_{MAX})	2 x 400 W _{MAX}
Power rating (P_{RMS})	2 x 250 W _{RMS}
Sensitivity	89 dB
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	0.28 mm/N
Moving mass (Mms)	199.5 g
Mech. Q factor (Qms)	2.81
Electr. Q factor (Qes)	0.31
Total Q factor (Qts)	0.28
Equivalent volume (Vas)	275 l
DC resistance (Re)	2 x 3.6 Ω /1 x 7.2 Ω
Force factor (BxL)	25.0 Tm
Voice coil induct. (Le)	2 x 1.1 mH/1 x 4.4 mH
Voice coil diameter	75.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 11.1 mm
Eff. cone area (Sd)	845 cm ²
Magnet weight	3.7 kg
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	\varnothing 402 mm x 180 mm
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	0-40 °C
Weight	11 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.