



SPX-20M

Order No.: 10.0930

EUR 62,90

RRP *

PRODUCTINFOS

Miniature hi-fi full range speaker, 15 W, 8 Ω

- Round steel basket with rear-ventilated centering spider
- Adhesive mounting or clamp mounting
- Inverse laminated cone
- Efficient neodymium drive system
- Perfect full range reproduction with an excellent efficiency in relation to its size
- 25 mm voice coil of high power capability

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-22,000 Hz
Resonant frequency (fs)	157 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P_{MAX})	30 W
Power rating (P_{RMS})	15 W
Sensitivity	87 dB
Max. rated SPL	-
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	0.76 mm/N
Moving mass (Mms)	1.3 g
Mech. Q factor (Qms)	4.52
Electr. Q factor (Qes)	0.46
Total Q factor (Qts)	0.42
Equivalent volume (Vas)	0.2 l
DC resistance (Re)	6.9 Ω
Force factor (BxL)	4.5 Tm
Voice coil induct. (Le)	0.13 mH
Voice coil diameter	\varnothing 25 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 0.5 mm
Eff. cone area (Sd)	13 cm ²
Magnet weight	neodymium
Magnet diameter	
Mounting cutout	
Mounting depth	
Mounting hole diameter	
Hole spacing X	
Hole spacing Y	
Dimensions	
Outside diameter	
Width	
Height	
Depth	
Admiss. ambient temp.	
Weight	0.17 kg
Quantity	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.