



SPX-31M

Order No.: 10.1660

EUR 26,90

RRP *

PRODUCTINFOS

Hi-fi full range speaker, 20 W, 8 Ω

- Excellent sound quality
- High-quality paper cone
- Aluminium phase plug for optimising the radiation pattern
- Rear-ventilated centering spider
- Magnet system with shielding
- Application in small speakers or satellite systems
- Ideally suited for application in FAST speakers (full range and subwoofer technology)

HOBBY HiFi 06/2015

"Ideally suited as a desktop speaker system.
Very neat workmanship."

TECHNICAL SPECIFICATIONS

Impedance (Z)	8 Ω
Operating voltage	-
Frequency range	f3-20,000 Hz
Resonant frequency (fs)	110 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Music power (P _{MAX})	40 W
Power rating (P _{RMS})	20 W
Sensitivity	86 dB
Max. rated SPL	-
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	0.92 mm/N
Moving mass (Mms)	1.9 g
Mech. Q factor (Qms)	3.707
Electr. Q factor (Qes)	0.69
Total Q factor (Qts)	0.58
Equivalent volume (Vas)	1.32 l
DC resistance (Re)	6.4 Ω
Force factor (BxL)	3.64 Tm
Voice coil induct. (Le)	0.18 mH
Voice coil diameter	\varnothing 20 mm
Voice coil former	Kapton
Linear excursion (X _{MAX})	\pm 1.1 mm
Eff. cone area (Sd)	32 cm ²
Magnet weight	119 g
Magnet diameter	
Mounting cutout	
Mounting depth	
Mounting hole diameter	
Hole spacing X	-
Hole spacing Y	-
Dimensions	
Outside diameter	
Width	
Height	

Depth

Admiss. ambient temp.

Weight 0.5 kg

Quantity

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.