

F SERIES


W4-1052SD



4" PP FULL RANGE

- FULL RANGE DESIGN
- STRUCTURED PP CONE WITH WIDE RANG TEMPERATURE RUBBER SURROUND, STABLE FO
- NEODYMIUM DESIGN,
- STAMPED STEEL BASKET
- MAGNETICALLY SHIELDED
- GOOD FOR HOME THeATER, MULTIMEDIA, CAR APPLICATION

DIAPHRAGM MTL	Structured pp
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	4W
DCR IMPEDANCE	3.8W
SENSITIVITY 1W/1m	87 dB
FREQUENCY RESPONSE	70-17KHz
FREE AIR RESONANCE	70 Hz
VOICE COIL DIAMETER	25.4 mm
AIR GAP HEIGHT	2.5 mm
RATED POWER INPUT	20 W
MAXIMUM POWER INPUT	40 W
FORCE FACTOR, BL	3.44 TM
MAGNET WEIGHT (oz)	Neodymium
MOVING MASS	3.85g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	1643 uMN ⁻¹
EFFEC.PISTON AREA	0.0057 M ²
Levc	0.061 mh
Zo	38 ohm
X-max	3.4 mm
Vas	7.58 Litr.
Qts	0.44
Qms	4.52
Qes	0.49



VOICE:886.2.26570282 FAX:886.2.26580166
E-MAIL :info@tb-speaker.com

CLOSE