



8" MID BASS

- HUGE FERRITE MAGNET, UNDER HUNG MOTOR DESIGN
- SHORT RING VC=38mm
- VERY LOW 2nd AND 3rd DISTORTION (LOW THD)
- LONG THROW, HIGH POWER LOADING, Xmax=9mm
- COATED PAPER CONE WITH WIDE RANGE TEMPERATURE OF FOAM RUBBER SURROUND

DIAPHRAGM MTL	Paper
SURROUND MTL	Foam Rubber
NOMINAL IMPEDANCE	4 W
DCR IMPEDANCE	3.6 W
SENSITIVITY 1W/1m	88 dB
FREQUENCY RESPONSE	35-3.5K Hz
FREE AIR RESONANCE	35 Hz
VOICE COIL DIAMETER	38.5 mm
AIR GAP HEIGHT	25 mm
RATED POWER INPUT	60 W
MAXIMUM POWER INPUT	120 W
FORCE FACTOR, BL	6.01 TM
MAGNET WEIGHT (65.7 oz)	1860 g
MOVING MASS	25.94 g
FERROFLUID ENHANCED	No
SUSPENSION COMPLIANCE	802.038 μMN^{-1}
EFFECTIVE PISTON AREA	0.022 M^2
Levc	0.111 mH
Zo	26 ohm
X-max	8.50 mm
Vas	55.12 Litr.
Qts	0.49
Qms	3.56
Qes	0.57



VOICE:886.2.26570282 FAX:886.2.26580166
E-MAIL :info@tb-speaker.com

CLOSE